

## **RARL-JEZ SERIES**

Efficiencies up to 16.5 SEER/13.0 EER **Nominal Sizes 2 to 5 Ton** [7.03 to 17.6 kW] **Cooling Capacities 25.2 to 59 kBTU** [7.38 to 17.29 kW]



## **Equipped with the** Comfort Control System™

- Increased system reliability and efficiency
  Exclusive Design with dual 7-segment LED display
- · Provides on board diagnostics and fault history

#### GENERAL TERMS OF LIMITED WARRANTY\*

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty. Conditional Unit Replacement

(Registration Required).....Ten (10) Years ......Ten (10) Years

\*For complete details of the Limited and Conditional Warranties, including applicable s and conditions, contact your local contractor or the Manufacturer of the product warranty certificate.

# Rheem *Prestige Series*™ Two-Stage Air **Conditioners equipped** with the Comfort Control System™


#### **Features:**

- The Comfort Control System™ provides on-board diagnostics and fault history for condensing units with single-phase compressors by detecting system and electrical problems without adding sensors. It can also communicate "fault codes" to enabled "L terminal" thermostats. The integrated diagnostics with Active Protection™ prevents compressor operation when damage would occur.
- 7-Segment LED Display is exclusive only to Rheem products. The informationdisplay quickly and accurately shows technicians the source of malfunctions.
- Ten-year conditional unit replacement warranty.
- Reliable Copeland Two-Stage Scroll™ Compressor for precise temperature control providing ultimate comfort.
- Comfort Alert™ Diagnostics comes installed in each Rheem *Prestige Series*™ model.
- All controls are accessible by removing one service panel. Removable top grille provides access to the condenser fan motor and condenser coil.
- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction, resulting in quiet fan operation.
- Exclusive Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain
- For quiet operation and improved efficiency, the 2, 3 and 4 ton models feature an  $\,$ 8-pole motor with a 3-blade outdoor fan.
- The 5 ton model features the GE® ECM two-speed motor with 3-blade outdoor fan.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.
- On-demand dehumidification terminal, when matched with a *Prestige Series*™ Air Handler or premium ECM Gas Furnace products, adjusts airflow to help control humidity for unsurpassed comfort in the cooling mode.

MODEL	Nominal Cooling Capacity (BTU/HR)	VOLTAGE	PHASE	HEIGHT	WIDTH	LENGTH	Shipping Weight	Service Valve - Liquid	Service Valve - Suction	PRICE
025JEZ	24,000	208/230	1	23"	31 - 1/2"	44 - 3/8"	210	3/8"	3/4"	
038JEZ	36,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	229	3/8"	3/4"	
049JEZ	48,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	265	3/8"	7/8"	
061JEZ	60,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	296	3/8"	7/8"	











sizing and installation of equipment is critical to achieve optimal performance. Ask your Contractor for details or visit www.en



ACCESSORIES									
Description	Part No.	Price							
Low Ambient Control (RXAD-A08)	RXAD-A08								
Crankcase Heater for 1.5 - 3 ton Models	44-17402-44								
Crankcase Heater for 3.5 - 5 ton Models	44-101884-01								

Total Price \$

