

RAPM-JEZ SERIES

Efficiencies up to 16 SEER/13.55 EER Nominal Sizes 1.5 to 5 Ton [5.28 to 17.6 kW] Cooling Capacities 18.8 to 62.5 kBTU [5.50 to 18.32 kW]



Equipped with the Comfort Control System™

- Increased system reliability and efficiency
- Exclusive Design with dual 7-segment LÉD display
- Provides on board diagnostics and fault history

GENERAL TERMS OF LIMITED WARRANTY*

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Conditional Compressor

(Registration Required)	Ten (10) Years
Parts	Ten (10) Years

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Rheem *Prestige Series*™ Air Conditioners equipped with the *Comfort*Control System™


Features:

- The Comfort Control System[™] provides on-board diagnostics and fault history for condensing units with single-phase compressors by detecting system and electrical problems without adding sensors. It can also communicate "fault codes" to enabled "L terminal" thermostats. The integrated diagnostics with Active Protection™ prevents compressor operation when damage would occur.
- 7-Segment LED Display is exclusive only to Rheem products. The informationdisplay quickly and accurately shows technicians the source of malfunctions.
- Five-year conditional unit replacement warranty.
- Compressor sound blanket is standard to provide quiet operation.
- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction.
- Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow
- Removable top grille provides access to the condenser fan motor and condenser coil.
- Single speed 8-pole fan motor designed for low speed, quiet, energy-saving operation.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

MODEL	Nominal Cooling Capacity (BTU/HR)	VOLTAGE	PHASE	HEIGHT	WIDTH	LENGTH	Shipping Weight	Service Valve - Liquid	Service Valve - Suction	PRICE
018JEZ	18,000	208/230	1	19"	27 - 5/8"	40 - 1/2"	160.5	3/8"	3/4"	
024JEZ	24,000	208/230	1	29"	31 - 1/2"	44 - 3/8"	214.5	3/8"	3/4"	
030JEZ	30,000	208/230	1	29"	31 - 1/2"	44 - 3/8"	214	3/8"	3/4"	
036JEZ	36,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	227	3/8"	7/8"	
042JEZ	42,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	256	3/8"	7/8"	
048JEZ	48,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	298	3/8"	7/8"	
056JEZ	56,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	306.5	3/8"	7/8"	
060JEZ	60,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	306.5	3/8"	7/8"	











"Proper sizing and installation of equipment is critical to achieve optimal performance. Ask your Contractor for details or visit www.energystar.gov."



ACCESSORIES					
Description	Part No.	Price			
Low Ambient Control (RXAD-A08)	RXAD-A08				
Crankcase Heater for 1.5 - 3 ton Models	44-17402-44				
Crankcase Heater for 3.5 - 5 ton Models	44-101884-01				

Total Price

\$		