

RANL- SERIES

Efficiencies up to 14.50 SEER/12.50 EER Nominal Sizes 1.5 to 5 Ton [5.28 to 17.6 kW] Cooling Capacities 18.3 to 62 kBTU [5.36 to 18.17 kW]



GENERAL TERMS OF LIMITED WARRANTY*

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Conditional Parts (Registration Required)Ten (10) Years

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Rheem *Classic® Series™* Air Conditioners


Features

The Rheem *Classic® Series* High Efficiency RANL- Condensing Units were designed with performance in mind. These units offer comfort, energy conservation and dependability for single, multi-family and light commercial applications.

- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction.
- Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- All controls are accessible by removing one service panel. Removable top grille provides access to the condenser fan motor and condenser coil.
- Single speed 8-pole fan motor designed for low speed, quiet, energy-saving operation.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

Model	Nominal Cooling Capacity (BTU/HR)	Voltage	Phase	Height	Width	Length	Shipping Weight	Service Valve - Liquid	Service Valve - Suction	Price
018	18,000 [5.28 kW]	208/230	1	19 [483]	233/4 [603]	351/2 [902]	140	3/8"	3/4"	
024	24,000 [7.03 kW]	208/230	1	19 [483]	275/8 [702]	401/2 [1029]	150	3/8"	3/4"	
031	30,000 [8.79 kW]	208/230	1	19 [483]	275/8 [702]	401/2 [1029]	152.5	3/8"	3/4"	
037CAZ 037DAZ 037JAZ	36,000 [10.55 kW]	208/230 208/230 460	1 3 3	23 [584]	311/2 [800]	44 ³ /8 [1127]	211.5	3/8"	3/4"	
043CAZ 043DAZ 043JAZ	42,000 [12.31 kW]	208/230 208/230 460	1 3 3	23 [584]	311/2 [800]	443/8 [1127]	210.5	3/8"	3/4"	
049CAZ 049DAZ 049JAZ 049YAZ	48,000 [14.07 kW]	208/230 208/230 460 575	1 3 3 3	29 [737]	311/2 [800]	443/8 [1127]	233.5	3/8"	7/8"	
060CAZ 060DAZ 060JAZ 060YAZ	60,000 [17.58 kW]	208/230 208/230 460 575	1 3 3 3	33 [383]	311/2 [800]	44 ³ /8 [1127]	260	3/8"	7/8"	









"Proper sizing and installation of equipment is critical to achieve optimal performance. Ask your Contractor for details or visit www.energystar.gov."



ACCESSORIES						
Description	Part No.	Price				
Low Ambient Control (RXAD-A08)	RXAD-A08					
Crankcase Heater for 1.5 - 3 ton Models	44-17402-44					
Crankcase Heater for 3.5 - 5 ton Models	44-101884-01					
Compressor Time Delay	RXMD-B01					

Total Price

\$		