



SALES FACT SHEET



RHKA- SERIES
featuring R-22 Refrigerant
RHKL- SERIES
featuring Earth-Friendly
R-410A Refrigerant



GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Indoor Coils leaks caused by factory defectsFive (5) Years
Electric Heating ElementFive (5) Years
*Any Other PartFive (5) Years

*In addition, a ten-year conditional parts warranty applies when the RHKL air handler is matched with a JEZ or JEC condensing unit or heat pump.

*For complete details of the limited warranty, including applicable terms & conditions, see your local installer or contact the manufacturer for a copy.

Features

- Includes an energy efficient GE® ECM® Motor, which in most applications, enhances the SEER rating of the outdoor unit. It also slowly ramps its speed up for quiet operation and enhanced customer satisfaction.
- Versatile 4-way convertible design for upflow, downflow, horizontal left and horizontal right applications.
- Nominal airflow up to 1.0" external static pressure.
- Factory-installed high efficiency indoor coil.
- Sturdy cabinet construction with 1.0 inch [25.4 mm] of foil faced insulation for excellent sound and insulating characteristics.
- Field-installed auxiliary electric heater kits provide exact heat for indoor comfort. Kits include circuit breakers which meet U.L. and cUL requirements for service disconnect.
- Dip switch settings for selectable, customized cooling airflow over a wide variety of applications.
- On-demand dehumidification terminal that adjusts airflow to help control humidity for unsurpassed comfort in cooling mode.

Price	Starting at: \$
-------	--------------------

<u>R</u>	<u>H</u>	<u>K</u>	<u>A</u>	<u>—</u>	<u>HM</u>	<u>24</u>	<u>17</u>	<u>J</u>	<u>A</u>
RHEEM	<u>CLASSIFICATION</u>	K = PREMIUM	REFRIGERANT	A/C OR HP	<u>CAPACITY</u>	<u>CABINET</u>	<u>VOLTAGE</u>	<u>DESIGN</u>	
	H = AIR HANDLER		A = R-22 L = R-410A	MULTI- POSITION (VERTICAL UPFLOW/ HORIZONTAL LEFT IS THE FACTORY CONFIGURATION)	24 = 18,000/24,000 BTU/HR [5.27/7.03 kW] 36 = 30,000/36,000 BTU/HR [6.79/10.55 kW] 48 = 42,000/48,000 BTU/HR [12.31/14.07 kW] 60 = 60,000 BTU/HR [17.58 kW]	17 = 17.5" [431.8 mm] (800-1200 CFM) 21 = 21" [533.4 mm] (1400-1600 CFM) 24 = 24.5" [609.6 mm] (1600-1800 CFM)	J = 208/240/1/60	A = 1ST DESIGN	

