



SALES FACT SHEET



Classic[®] Plus

AIR HANDLERS

RHLA- High Efficiency

featuring R-22 Refrigerant

RHLL- High Efficiency

featuring Earth-Friendly
R-410A Refrigerant



Features

- RHLA/RHLL models feature GE's new X-13 motor which provides enhanced SEER performance with most Rheem outdoor units.
- 1 1/2 ton [5.3 kW] through 5 ton [17.6 kW] models are between 42 1/2 to 55 1/2 inches [1080 to 1410 mm] tall and 22 inches [559 mm] deep.
- Versatile 4-way convertible design for upflow, downflow, horizontal left and horizontal right applications.
- Factory-installed high efficiency indoor coil.
- All models meet or exceed 330 to 400 CFM [156 to 189 L/s] per ton at .3 inches [.7 kPa] of external static pressure.
- Enhanced airflow up to .7" external static pressure.
- Sturdy construction with 1.0 inch [.24 kPa] of reinforced foil faced jacket insulation for excellent thermal and sound insulation.
- Field-installed auxiliary electric heater kits provide exact heat for indoor comfort. Kits include circuit breakers which meet UL and cUL requirements for service disconnect.
- The most compact unit design available, all standard heat air handler models only 42 1/2 to 55 1/2 inches [1079 to 1409 mm] high.
- Attractive pre-painted cabinet exterior.
- Rugged wall steel cabinet construction, designed for added strength and versatility.

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Indoor Coils leaks caused by factory defects Five (5) Years
Electric Heating Element Five (5) Years
Any Other Part Five (5) Years

For Complete Details of the Limited Warranty, including Applicable Terms & Conditions, See Your Local Installer or Contact the Manufacturer for a Copy.

<u>R</u>	<u>H</u>	<u>L</u>	<u>A</u>	<u>—</u>	<u>HM</u>	<u>24</u>	<u>17</u>	<u>J</u>	<u>A</u>
RHEEM	CLASSIFICATION	L = HI-EFFICIENCY (X-13 MOTOR)	REFRIGERANT	A/C OR HP	CAPACITY	CABINET SIZE	VOLTAGE	DESIGN VARIATION	
	H = AIR HANDLER		A = R-22 L = R-410A	MULTI-POSITION (VERTICAL UPFLOW/HORIZONTAL LEFT IS THE FACTORY CONFIGURATION)	24 = 18,000/24,000 BTU/HR [5.27/7.03 kW] 36 = 30,000/36,000 BTU/HR [6.79/10.55 kW] 48 = 42,000/48,000 BTU/HR [12.31/14.07 kW] 60 = 60,000 BTU/HR [17.58 kW]	17 = 17.5" [431.8 mm] (800-1200 CFM) 21 = 21" [533.4 mm] (1400-1600 CFM) 24 = 24.5" [609.6 mm] (1600-1800 CFM)	A = 115/1/60 J = 208/240/1/60	A = 1ST DESIGN	

Price	Starting at: \$
-------	--------------------



"CERTIFIED UNDER THE
A.R.I. CERTIFICATION PROGRAM—A.R.I.
STANDARDS 210/240-84"

