SALES FACT SHEET



RQNM-

13 SEER Series Nominal Sizes 2-5 Tons [7-17.6 kW]

RQPM-

14 SEER Series Nominal Sizes 2-5 Tons [7-17.6 kW]

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Compressor, 1 Phase, Residential Applications	Ten (10) Years
13 & 14 SEER, Commercial Applications	Five (5) Years
Any Other Part	
1 Phase, Residential Applications	
1 & 3 Phase. Commercial Applications	

Classic[®]

Featuring Earth-Friendly R-410A Refrigerant



Features

The Rheem *Classic Series*[®] RQNM- & RQPM- Package Heat Pumps can provide year-round heating and cooling comfort for residential, multi-family and light commercial applications.

The following additional features, plus its energy-saving characteristics, make the RQNM- & RQPM- Package Heat Pumps an excellent choice for new construction or upgrading your present system.

- Scroll Compressor
- Copper Tube/Aluminum Fin Coils
- Powder painted louvered steel cabinet protects coil from damage
- Painted Base Pan
- Demand Defrost Control
- Non-Cycling Reversing Valve
- Gauge Ports
- Control box is fully accessible
- Power and control wiring are kept separate
- Certified and rated under ARI Standard 240
- U.L. listed
- Factory run tested prior to shipment

<u>R</u>	Q	N	Μ	<u>– A</u>	<u>036</u>		Ī	<u>K</u>	<u>010</u>
RHEEM	PRODUCT CLASSIFICATION Q = PACKAGE HEAT PUMP		DESIGN <u>SERIES</u> M = R-410A	FUTURE TECHNICAL VARIATIONS	NOMINAL COOLING 024 = 24,000 BTU/H 030 = 30,000 BTU/H 036 = 36,000 BTU/H 042 = 42,000 BTU/H 048 = 48,000 BTU/H 060 = 60,000 BTU/H	[7.03 kW] [8.79 kW] J [10.55 kW] [12.31 kW] C [14.07 kW]	1PH—60 Hz	DRIVE <u>PACKAGE</u> K = DIRECT DRIVE	HEATING CAPACITY (FACTORY INSTALLED) 000 = No Resistance Heat 005 = 05 KW Resistance Heat 007 = 07 KW Resistance Heat 010 = 10 KW Resistance Heat 015 = 15 KW Resistance Heat 020 = 20 KW Resistance Heat
							Price	Startin \$	ıg at:
Accredited	by the Rel BSO 9001:2 Certificate Number		Seasonal Energ	RGUIDE gy Efficiency Ratio (SEER) rs least energy →21.0	ENERQUIDE Seasonal Energy Efficiency Ratio (SEER) 100 13.0 — Uses least energy →21.0	energy (14 SE	ENERGY STAR PARTNER EER ONLY)	PERFORMANCE CERTIFICAL Al Standard 2012/04 British British Andre St Water British Andre St Water British Andre St Water British Andre St Water British Andre St	C UL US LISTED

RHEEM AIR CONDITIONING DIVISION 5600 Old Greenwood Road, Fort Smith, Arkansas 72908