

inverTITAN

POWERFUL PERFORMANCE. EFFICIENT OPERATION.

Designed and engineered to meet the highest requirements for cooling and heating options, with full inverter compressor and top discharge fans for a streamlined efficient air flow. Powerful performance supported by the latest eco-friendly technology. Enjoy new possibilities for pool heating and cooling with the space saving and slick design of the InverTITAN. Limited space is no longer a concern. Full Stepless DC Compressor, marine grade aluminium alloy casing, Twisted Titanium Heat Exchanger and Madimack's Advanced Sound Suppression Technology for whisper quiet operation.

Trusted by
POOL PROFESSIONALS



Heat & Cool

With integrated heating and cooling into a single unit, enjoy your swimming pool any season of the year



Operation down to 14°F

Built to operate in the coldest weather and extend your pool season into the winter



Built-in Wi-Fi

Built-in Wi-Fi and a smart app provide convenience to control your pump on-the-go



Twin-rotary compressor

Significantly reduced operating noise



Electronic expansion valve

Optimized flow of refrigerant 20% higher COP



Twisted titanium heat exchanger

Increased area for heat exchange 40% higher efficiency



Smart & quick defrosting

InverTITAN is equipped with reverse cycle defrosting detecting frost accumulation during operation and automatically switch to defrosting mode



**advanced
sound
suppression
technology**



madimack

Powered by

invermac
TECHNOLOGY



TECHNICAL PARAMETERS

Model		InverTitan 90,000	InverTitan 112,000	InverTitan 140,000
SKU		INVTIT090	INVTIT112	INVTIT140
PERFORMANCE CONDITION: Air 80°F (26.7°C)/ Water 80°F (26.7°C)/ Humidity 80%				
Heating capacity (BTU)		90,000	112,000	140,000
COP Range		14.3 ~ 6.0	14.5 ~ 6.1	14.6 ~ 6.0
PERFORMANCE CONDITION: Air 80°F (26.7°C)/ Water 80°F (26.7°C)/ Humidity 63%				
Heating capacity (BTU)		85,000	106,000	134,000
COP Range		12.7 ~ 5.7	12.8 ~ 5.8	13.3 ~ 5.7
PERFORMANCE CONDITION: Air 50°F (10°C)/ Water 80°F (26.7°C)/ Humidity 63%				
Heating capacity (BTU)		46,000	56,000	69,000
COP Range		5.3 ~ 4.6	5.4 ~ 4.8	5.6 ~ 4.7
TECHNICAL SPECIFICATIONS				
Operating air temperature (°F)		14 ~ 109		
Heat exchanger		Titanium in PVC		
Power supply		208V ~ 230V/1 Ph/60Hz		
Water connection (mm)/(inch)		50mm/2"		
Rated input power at air 80°F (26.7°C) (kW)		0.63~4.28	0.6~5.4	0.8~6.9
Rated input current at air 80°F (26.7°C) (A)		2.88~18.6	2.9~23.7	3.6~31.3
Sound level at 10ft (3.05m) dB(A)		34.3 ~ 46.5	35.2 ~ 48.3	38.8 ~ 51.1
Advised water flux	(L/min)	125 ~ 158	133~167	133 ~ 254
	(GPM)	33.0 ~41.7	35.1 ~ 44.1	35.1 ~ 67.1
Net dimension L x W x H	(mm)	906 × 701 × 977	906 × 701 × 977	992 × 806 × 1054
	(inch)	35.7" × 27.6" × 38.5"	35.7" × 27.6" × 38.5"	39.1" × 31.7" × 41.5"
Net weight	(kg)	126	125	143
	(lb)	277.8	275.6	315.3
Maximum air volume(m³/h)		6500	7500	8300
Water pressure drop(Kpa)		6	10	19

Remarks: The data above is only for reference. For specific data, please refer to the nameplate on the unit.

madimack